

VII. Cooperation & Competition

The Iterated Prisoner's Dilemma

2012/4/25

1

The Prisoners' Dilemma

- Devised by Melvin Dresher & Merrill Flood in 1950 at RAND Corporation
- Further developed by mathematician Albert W. Tucker in 1950 presentation to psychologists
- It “has given rise to a vast body of literature in subjects as diverse as philosophy, ethics, biology, sociology, political science, economics, and, of course, game theory.” — S.J. Hagenmayer
- “This example, which can be set out in one page, could be the most influential one page in the social sciences in the latter half of the twentieth century.” — R.A. McCain

2012/4/25

2

Prisoners' Dilemma: The Story

- Two criminals have been caught
- They cannot communicate with each other
- If both confess, they will each get 10 years
- If one confesses and accuses other:
 - confessor goes free
 - accused gets 20 years
- If neither confesses, they will both get 1 year on a lesser charge

2012/4/25

3

Prisoners' Dilemma Payoff Matrix

		Bob	
		cooperate	defect
Ann	cooperate	-1, -1	-20, 0
	defect	0, -20	-10, -10

- defect = confess, cooperate = don't
- payoffs < 0 because punishments (losses)

2012/4/25

4

Ann's "Rational" Analysis (Dominant Strategy)

		Bob	
		cooperate	defect
Ann	cooperate	-1, -1	-20, 0
	defect	0, -20	-10, -10

- if cooperates, may get 20 years
- if defects, may get 10 years
- ∴, best to defect

2012/4/25

5

Bob's "Rational" Analysis (Dominant Strategy)

		Bob	
		cooperate	defect
Ann	cooperate	-1, -1	-20, 0
	defect	0, -20	-10, -10

- if he cooperates, may get 20 years
- if he defects, may get 10 years
- ∴, best to defect

2012/4/25

6

Suboptimal Result of “Rational” Analysis

		Bob	
		cooperate	defect
Ann	cooperate	-1, -1	-20, 0
	defect	0, -20	-10, -10

- each acts individually rationally \Rightarrow get 10 years (dominant strategy equilibrium)
- “irrationally” decide to cooperate \Rightarrow only 1 year

2012/4/25

7

Summary

- Individually rational actions lead to a result that all agree is less desirable
- In such a situation you cannot act unilaterally in your own best interest
- Just one example of a (game-theoretic) *dilemma*
- Can there be a situation in which it would make sense to cooperate unilaterally?
 - **Yes**, if the players can expect to interact again in the future

2012/4/25

8

The Iterated Prisoners' Dilemma

and Robert Axelrod's Experiments

2012/4/25

9

Assumptions

- No mechanism for enforceable threats or commitments
- No way to foresee a player's move
- No way to eliminate other player or avoid interaction
- No way to change other player's payoffs
- Communication only through direct interaction

2012/4/25

10

Axelrod's Experiments

- Intuitively, expectation of future encounters may affect rationality of defection
- Various programs compete for 200 rounds
 - encounters each other and self
- Each program can remember:
 - its own past actions
 - its competitors' past actions
- 14 programs submitted for first experiment

2012/4/25

11

IPD Payoff Matrix

		B	
		cooperate	defect
A	cooperate	3, 3	0, 5
	defect	5, 0	1, 1

N.B. Unless $DC + CD < 2 CC$ (i.e. $T + S < 2R$), can win by alternating defection/cooperation

2012/4/25

12

Indefinite Number of Future Encounters

- Cooperation depends on expectation of **indefinite** number of future encounters
- Suppose a known finite number of encounters:
 - No reason to C on last encounter
 - Since expect D on last, no reason to C on next to last
 - And so forth: there is no reason to C at all

2012/4/25

13

Analysis of Some Simple Strategies

- Three simple strategies:
 - **ALL-D**: always defect
 - **ALL-C**: always cooperate
 - **RAND**: randomly cooperate/defect
- Effectiveness depends on environment
 - **ALL-D** optimizes local (individual) fitness
 - **ALL-C** optimizes global (population) fitness
 - **RAND** compromises

2012/4/25

14

Expected Scores

↓ playing ⇒	ALL-C	RAND	ALL-D	Average
ALL-C	3.0	1.5	0.0	1.5
RAND	4.0	2.25	0.5	2.25
ALL-D	5.0	3.0	1.0	3.0

2012/4/25

15

Result of Axelrod's Experiments

- Winner is Rapoport's **TFT** (Tit-for-Tat)
 - cooperate on first encounter
 - reply in kind on succeeding encounters
- Second experiment:
 - 62 programs
 - all know **TFT** was previous winner
 - **TFT** wins again

2012/4/25

16

Expected Scores

↓ playing ⇒	ALL-C	RAND	ALL-D	TFT	Avg
ALL-C	3.0	1.5	0.0	3.0	1.875
RAND	4.0	2.25	0.5	2.25	2.25
ALL-D	5.0	3.0	1.0	$1+4/N$	2.5+
TFT	3.0	2.25	$1-1/N$	3.0	2.3125-

2012/4/25

N = #encounters

17

Demonstration of Iterated Prisoners' Dilemma

[Run NetLogo demonstration
PD N-Person Iterated.nlogo](#)

2012/4/25

18

Characteristics of Successful Strategies

- *Don't be envious*
 - at best **TFT** ties other strategies
- *Be nice*
 - i.e. don't be first to defect
- *Reciprocate*
 - reward cooperation, punish defection
- *Don't be too clever*
 - sophisticated strategies may be unpredictable & look random; be clear

2012/4/25

19

Tit-for-Two-Tats

- More forgiving than **TFT**
- Wait for two successive defections before punishing
- Beats **TFT** in a noisy environment
- E.g., an unintentional defection will lead **TFTs** into endless cycle of retaliation
- May be exploited by feigning accidental defection

2012/4/25

20

Effects of Many Kinds of Noise Have Been Studied

- Misimplementation noise
- Misperception noise
 - noisy channels
- Stochastic effects on payoffs
- General conclusions:
 - sufficiently little noise \Rightarrow generosity is best
 - greater noise \Rightarrow generosity avoids unnecessary conflict but invites exploitation

2012/4/25

21

More Characteristics of Successful Strategies

- Should be a generalist (robust)
 - i.e. do sufficiently well in wide variety of environments
- Should do well with its own kind
 - since successful strategies will propagate
- Should be cognitively simple
- Should be evolutionary stable strategy
 - i.e. resistant to invasion by other strategies

2012/4/25

22

Kant's Categorical Imperative

“Act on maxims that can at the same time have for their object themselves as universal laws of nature.”

2012/4/25

23

Ecological & Spatial Models

2012/4/25

24

Ecological Model

- What if more successful strategies spread in population at expense of less successful?
- Models success of programs as fraction of total population
- Fraction of strategy = probability random program obeys this strategy

2012/4/25

25

Variables

- $P_i(t)$ = probability = proportional population of strategy i at time t
- $S_i(t)$ = score achieved by strategy i
- $R_{ij}(t)$ = relative score achieved by strategy i playing against strategy j over many rounds
 - fixed (not time-varying) for now

2012/4/25

26

Computing Score of a Strategy

- Let n = number of strategies in ecosystem
- Compute score achieved by strategy i :

$$S_i(t) = \sum_{k=1}^n R_{ik}(t)P_k(t)$$

$$\mathbf{S}(t) = \mathbf{R}(t)\mathbf{P}(t)$$

2012/4/25

27

Updating Proportional Population

$$P_i(t+1) = \frac{P_i(t)S_i(t)}{\sum_{j=1}^n P_j(t)S_j(t)}$$

2012/4/25

28

Some Simulations


- Usual Axelrod payoff matrix
- 200 rounds per step

2012/4/25

29

Demonstration Simulation

- 60% ALL-C
- 20% RAND
- 10% ALL-D, TFT



2012/4/25

30

NetLogo Demonstration of Ecological IPD

[Run EIPD.nlogo](#)

2012/4/25

31

Collectively Stable Strategy

- Let w = probability of future interactions
- Suppose cooperation based on reciprocity has been established
- Then no one can do better than **TFT** provided:

$$w \geq \max\left(\frac{T - R}{R - S}, \frac{T - R}{T - P}\right)$$

- The **TFT** users are in a Nash equilibrium

2012/4/25

32

“Win-Stay, Lose-Shift” Strategy


- Win-stay, lose-shift strategy:
 - begin cooperating
 - if other cooperates, continue current behavior
 - if other defects, switch to opposite behavior
- Called **PAV** (because suggests Pavlovian learning)

2012/4/25

33

Simulation without Noise

- 20% each
- no noise



2012/4/25

34

Effects of Noise

- Consider effects of noise or other sources of error in response
- **TFT:**
 - cycle of alternating defections (CD, DC)
 - broken only by another error
- **PAV:**
 - eventually self-corrects (CD, DC, DD, CC)
 - can exploit **ALL-C** in noisy environment
- Noise added into computation of $R_{ij}(t)$

2012/4/25

35


Flake's Simulation with Noise

- $R(t)$ is computed over r rounds
- $A_{ik}(j)$ = action of strategy i playing against strategy k in round j
 - Normal strategy i action with probability $1 - p_n$
 - Random C/D with probability p_n
- Note that this overestimates effects of noise

$$R_{ik}(t) = \sum_{j=1}^r \text{payoff}[A_{ik}(j)A_{ki}(j)]$$

2012/4/25

36



Run Flake's EIPD with Noise

EIPD-cbn.nlogo

2012/4/25
38

Spatial Effects

- Previous simulation assumes that each agent is equally likely to interact with each other
- So strategy interactions are proportional to fractions in population
- More realistically, interactions with “neighbors” are more likely
 - “Neighbor” can be defined in many ways
- Neighbors are more likely to use the same strategy

2012/4/25

39

Spatial Simulation

- Toroidal grid
- Agent interacts only with eight neighbors
- Agent adopts strategy of most successful neighbor
- Ties favor current strategy

2012/4/25

40


NetLogo Simulation of Spatial IPD

[Run SIPD-async-alter.nlogo](#)

2012/4/25

41

Typical Simulation ($t = 1$)



Colors:

ALL-C

TFT

RAND


PAV

ALL-D

2012/4/25

42

Typical Simulation ($t = 5$)



Colors:

ALL-C

TFT

RAND


PAV

ALL-D

2012/4/25

43

Typical Simulation ($t = 10$)



Colors:

ALL-C

TFT

RAND

PAV

ALL-D

2012/4/25

44


Typical Simulation ($t = 10$) Zooming In



2012/4/25

45

Typical Simulation ($t = 20$)



Colors:

ALL-C

TFT

RAND


PAV

ALL-D

2012/4/25

46

Typical Simulation ($t = 50$)



Colors:

ALL-C

TFT

RAND

PAV


ALL-D

2012/4/25

47


Typical Simulation ($t = 50$)

Zoom In



2012/4/25

48



Conclusions: Spatial IPD

- Small clusters of cooperators can exist in hostile environment
- Parasitic agents can exist only in limited numbers
- Stability of cooperation depends on expectation of future interaction
- Adaptive cooperation/defection beats unilateral cooperation or defection

NetLogo Simulation of Spatial IPD

[Run SIPD-async-alter.nlogo](#)

2012/4/25

51

Additional Bibliography

1. von Neumann, J., & Morgenstern, O. *Theory of Games and Economic Behavior*, Princeton, 1944.
2. Morgenstern, O. "Game Theory," in *Dictionary of the History of Ideas*, Charles Scribners, 1973, vol. 2, pp. 263-75.
3. Axelrod, R. *The Evolution of Cooperation*. Basic Books, 1984.
4. Axelrod, R., & Dion, D. "The Further Evolution of Cooperation," *Science* **242** (1988): 1385-90.
5. Poundstone, W. *Prisoner's Dilemma*. Doubleday, 1992.

2012/4/25

Part VIIB

52