Physical Neural Networks

David Perryman COSC 594




Presentation Overview

- Motivation and Context
- Historical Perspective
- State-of-the-Art
- Future Prospects



What are physical neural networks?

Physical Neural Networks can be broadly described as any physical circuit built to emulate the neural connections of a brain.






Why use neural networks?


Neural networks have been successful both because of their parallelism that enabled implementation on GPUs and because of their versatility at a variety of tasks, from beating humans at games, identifying photos, and natural language processing.





[1]. Google Trends.https://trends.google.com/trends/?geo=US





[7] A million spiking-neuron integrated circuit with a scalable communication network and interface. DOI: 10.1126/science.1254642


THE UNIVERSITY OF TENNESSEE


Why use <u>physical</u> neural networks?

- Energy Considerations drive modern computing advances, and physical neural nets could improve energy efficiencies.
- "Torturing the medium"
- Offers a new paradigm for computing



Why use <u>physical</u> neural networks?





Proposal For Neuromorphic Hardware Using Spin Devices. Mrigank` Sharad, Charles Augustine, Georgios Panagopoulos, Kaushik Roy




Advantages/Disadvantages

Physical Neural Networks (PNNs) are still being developed, so their advantages and disadvantages are commensurate with other developing technologies. The most important features are:

- "economy of scale"
- Energy savings
- Flexibility in training (both good and bad)
- New paradigm



How do neural nets work?



$$o_i = w_i^i x$$

$$y_i = \frac{\exp o_i}{\sum_k \exp o_k}$$

By adding enough nodes, a neural network can learn any relationship between the training set and the output.

[4] Introduction to Machine Learning. Alpaydin. 3rd Edition. Pg 271.



How do physical neural nets

work?

Modern chips are:

- Asynchronous
- Spiking neuron
- Integrated with von Neumann machines
- Large scale




Fig. 4. Benchmarking power and energy. (A) Example network topology used for benchmarking power at real-time operation. Nodes represent cores, and edges represent neural connections; only 64 of 4096 cores are shown. (B) Although power remains low (<150 mW) for all benchmark networks, those with higher synaptic densities and higher spike rates consume more total power, which illustrates that power consumption scales

with neuron activity and number of active synapses. (C) The total energy (passive plus active) per synaptic event decreases with higher synaptic density because leakage power and baseline core power are amortized over additional synapses. For a typical network where neurons fire on average at 20 Hz and have 128 active synapses [marked as * in (B) and (C)], the total energy is 26 pJ per synaptic event.




How do physical neural nets

work?

Can implement <u>mathematically</u> identical

processes in physical neural nets



Emulation of neural network using spin-CMOS hybrid circuit: In each neuron, the MTJ acts as the firing site, i.e., the nucleolus; DWM stripe can be compared to cell body and its spin polarization state is analogous to electrochemical potential in the neuron cell body which affects 'firing', the CMOS detection unit can be compared to axon that transmits electrical signal to the receiving neuron, and finally a weighted transistor acts as synapse as it determines the amount of current injected into a receiving neuron.

Proposal For Neuromorphic Hardware Using Spin Devices. Mrigank` Sharad, Charles Augustine, Georgios Panagopoulos, Kaushik Roy



Historical Perspective

- 1943. McCulloch and Pitts model neurons with electrical circuits
- 1948. Turing describes "Intelligent Machinery" with artificial neurons
- 1949. Hebb writes "The Organization of Behavior" and notices that neural

pathways are strengthened at each use.

[5] Neural Networks: History. Eric Roberts. https://cs.stanford.edu/people/eroberts/

[6] "Intelligent Machinery". Alan Turing.



Historical Perspective

- 1959. Widrow and Hoff develop "ADELINE" and "MADALINE" (Multiple ADAptive LINear Elements). MADALINE used an adaptive filter that eliminates echoes on phone lines.
- 1972. Kohonen and Anderson independently describe arrays of analog PNNS



Historical Irony

John von Neumann suggested the imitation of neural functions by using telegraph relays or vacuum tubes.



What is being done now?


- 2014. IBM has published a neuromorphic chip, "True North", that implements 1 million neurons.
- 2017. Intel has released a neuromorphic chip, "Loihi", that has adaptive self-modifying parallelism.

[7] A million spiking-neuron integrated circuit with a scalable communication network and interface. DOI: 10.1126/science.1254642

[8] Loihi: A Neuromorphic Manycore Processor with On-Chip Learning. DOI: <u>10.1109/MM.2018.112130359</u>



What is being done now?



The design process for the True North Chip.

[7] A million spiking-neuron integrated circuit with a scalable communication network and interface. DOI: 10.1126/science.1254642



What are some prospects for Physical Neural Networks?

- Compilers
- Accessibility
- "Economy of Scale"
- Integration with von Neumann architecture
- Physical implementation of algorithms
- plasticity



What are some prospects for Physical Neural Networks?

Neuromorphic computing is continuing:

- BRAIN initiative proposed by Obama administration
- True North and Loihi
- Medical/Computer Science interest
- DARPA/DOD/DOE



References

- [1]. Google Trends.
- https://trends.google.com/trends/?geo=US
- [2] Historical and extrapolated switching energy. Figure. Frank (2005b, slide 9)
- [3] Proposal For Neuromorphic Hardware Using Spin Devices. Mrigank` Sharad, Charles Augustine, Georgios Panagopoulos, Kaushik Roy



References

- [4] Introduction to Machine Learning. Alpaydin. 3rd Edition. Pg 271.
- [5] Neural Networks: History. Eric Roberts.
- https://cs.stanford.edu/people/eroberts/
- [6] "Intelligent Machinery". Alan Turing.

http://www.alanturing.net/turing_archive/archive/l

<u>/I32/L32-002.html</u>



References

[7] A million spiking-neuron integrated circuit with a scalable communication network and interface. DOI: 10.1126/science.1254642

[8] Loihi: A Neuromorphic Manycore Processor with On-Chip Learning. DOI: <u>10.1109/MM.2018.112130359</u>

